



ES3214E

Paved surface scissor lift

LIST OF STANDARD EQUIPMENT

- Automatic stabilizers to work at height
- Automatic pothole protection system
- Crushing protection
- High ground clearance
- Self-locking door on the platform
- Speed limit at maximum height
- Platform load sense system
- Automatic braking system
- Emergency brake release
- Non-marking tyres
- Tilt indicator with alarm
- Warning siren during lowering and dual flashing LED light
- Safety bracket for maintenance operations
- Horn
- Cylinder locking valve
- Emergency stop button
- Emergency lowering
- Traction engine protection
- Anchoring eyebolts
- Onboard diagnostics system
- Hour counter
- Proportional controls
- Fold-down guardrails
- Power to platform
- Lithium battery - Maintenance free
- Explosion-proof tubing system
- Motion Alarm
- Charging protection system
- Charging indicator
- Tie-down and lifting points
- One way platform extension deck
- Four-wheel drive
- Four-wheel steering
- Self-weight lowering system
- Emergency pump



LOGISTICS



CONSTRUCTION

ES3214E




Load capacity		750 kg
Load capacity when extended		750 kg
Max no. Occupants (Indoor/outdoor)		2/2
Working height	A	32 m
Platform floor level height	B	30 m
Overall length	C	6.41 m
Overall width	D	1.39 m
Overall height (rails up)	E	4.16 m
Transport height (rails down)	F	3.17 m
Platform dimensions (length/width)		5.85x1.2 m
Platform extension	G	1.9 m
Ground clearance (stowed)		19 cm
Ground clearance (raised)		2.0 cm
Wheelbase	H	4.87 m
Turning radius (inside)		2.6 m
Turning radius (outside)		3.5 m
Driving motors		4x53VAC/2kW
Lifting motors		53VAC/28kW
Travel speed (stowed)		1,4 km/h
Travel speed (raised)		0,1 km/h
Batteries		80V/520Ah Lithium Battery
Integrated battery charger		80V/80A
Gradeability		30%
Maximum working slope		1°(0°)
Non-marking tyres		28X12 - 22
Weight (CE)		22,200 kg



Standard stabilisers



Safety bracket



STANDARDS MET: EN 280-1, ANSI/SAIA A92.20

The data given in this brochure are provided for information purposes and are subject to change without prior notice. All images are purely guideline and might not give an exact representation of the product.